

LIMITED WARRANTY
Poly Processing Company

Poly Processing Company Product	Warranty Period
CROSSLINKED POLYETHYLENE TANKS for all suitable applications except those listed below	5 yrs
IMFO® TANKS STORING SODIUM HYPOCHLORITE 9 – 15 wt% (refer to PPC Position Statement) <u>HDXLPE w/ OR-1000™</u> , 1.9 spg rating	5 yrs
NON-IMFO® TANKS STORING SODIUM HYPOCHLORITE 9 – 15 wt% (refer to PPC Position Statement) 1000 gallons and larger: <u>HDXLPE w/ OR-1000™</u> , 1.9 spg rating Less than 1000 gallons: <u>HDXLPE</u> 1.9 spg rating	3 yrs
TANKS STORING SULFURIC ACID ≥ 80% CONCENTRATION (refer to PPC Position Statement) SAFE-TANK® to 8700 gallons: <u>HDXLPE w/ OR-1000™</u> , 2.2 spg rating Vertical tanks 1000 - 6600 gallons: <u>HDXLPE w/ OR-1000™</u> , 2.2 spg rating Vertical tanks less than 1000 gallons: <u>HDXLPE</u> 1.9 spg rating	3 yrs
TANKS STORING HYDROCHLORIC ACID ≤ 37% CONCENTRATION (refer to PPC Position Statement) <u>HDXLPE w/ OR-1000™</u> , 1.9 spg rating	5 yrs
TANKS STORING HYDROCHLORIC ACID ≤ 37% CONCENTRATION (refer to PPC Position Statement) <u>HDXLPE</u> 1.9 spg rating	3 yrs
LINEAR POLYETHYLENE TANKS - for all suitable applications except Sodium Hypochlorite 9 – 15%; Sulfuric Acid and Hydrochloric Acid of any concentration	3 yrs

Poly Processing Company's warranty consists of repair or replacement of defective product. Owner and/or user may be requested to provide a cleaned section of the product in question for evaluation. Product disposal or alternate use is the owner and/or user's responsibility. Warranty begins at date of shipment from PPC plant. Parts and ancillary items are warranted for ninety (90) days.

Poly Processing Company's liability is limited to either repair or replacement of its product. By accepting delivery of the product, owner and/or user waives any claim against PPC for incidental or consequential damages as they relate to lost profits or sales or to injury of persons or property, including secondary containment. Owner and/or user accepts full responsibility for providing secondary containment appropriate and adequate for the stored material.

This warranty will be nullified if:

1. Product has been used in manner other than its originally declared purpose or if PPC tank recommendations have not been followed.
2. Product has not been installed, used, and maintained in accordance with a) all federal, state, and local laws and regulations; b) generally accepted best practices within the applicable industry; c) guidelines set forth in the PPC Installation Manual and/or in PPC Position Statements.
3. Product has been altered or repaired by unauthorized personnel.
4. Notification of the defect has not been made in writing within the warranty period.
5. Invoice for product has not been paid.
6. Product has been subjected to misuse, negligence, fire, accident, act of war, or act of God.

The limited warranty described herein is Poly Processing Company's sole warranty and the complete, final and exclusive statement of the terms of the warranty. Owner and/or user may not rely on any oral statement or representations. This warranty is neither assignable nor transferable.

Issued: November 1, 2006