


NOTES

1. THIS IS A COMPUTER GENERATED DWG. DO NOT REVISE BY HAND.
2. BOLTING TO BE 1/2-13 X 3 1/4" LG ALL TH'D STUD W/PE ENCAPSULATED HEAD W/FLAT WASHER, LOCK WASHER & 1/2-13 NUT/316SS, ALLOY C-276, TITANIUM, OR ALLOY 400 W/STUD BOLT GSKT/3/8" THK PE FOAM OR EPDM SPONGE;
3. COVER GSKTS TO BE 23" OD X 17" ID FOR 17" MANWAY, 32" OD X 24" ID FOR 24" MANWAY. GSKT MAT'L TO BE 3/8" THK PE FOAM OR EPDM SPONGE; 1/4" THK EPDM, VITON OR BUNA-N.

REV "C" DELETED 24" PE COVER & BOLT RING/ADDED FRP COVER BY:JB1 1/16/WM
 REV "B" ADDED SUPP'T RING BY:JB 5/3/12 CK:CD
 REV "A" REVISED NOTE BY:JB 1/29/09 CK:WM

DWG TITLE		17" & 24" FUME TIGHT MANWAY COVERS	
SCALE:	2"=1'-0"	 Central Region P.O. Box 4580 47163 2251 Old Springington Rd. Norcross, GA 30052 CSB: 343-7825 FAX CSB: 343-9795	DR: MB WILKERSON
DATE:	10/11/00		CK: J. BRANTLEY
SHEET		COMPUTER FILE	REV
1 OF 1		17-24FTMWY	C